



ULTRABENDER PRO

HIGH BENDING ACCURACY

Precision ground ballscrew to incorporate with professional die making software to acquire high accuracy demand

HIGH BALANCING FLATNESS

Integrated more than 20 years of die making experience to achieve high balancing flatness of dies

WIDE RANGE OF RULES SUPPORT

Can operate for label rules, normal cutting rules, high rules and thick rules

NEW CUTTING SYSTEM

New cutting unit for up to 12 tools and auto selection by software

FAST CHANGING TOOLS

Fast, easy and convenient way of changing tools for using different types of rules

TWO WAYS OF CUTTING

Two-segment cutting function and full-cut function for maintaining length accuracy during bending as well as cutting efficiency



ULTRABENDER PRO

FEATURES

- Full Cut
- Cut Crease
- Auto Perforate Deepness
- Auto Bridge Height & Width
- High Rule, Label Rule and Thick Rule
- Auto-Broach Deepness
- Dual Broaching and Nicking Function

TECHNICAL DATA

Supported rule height	7 – 60 mm (0.45 – 1.07 mm Thick), 12 – 32 mm (0.45 – 1.42 mm Thick)
Broaching	“V” shape & “Flat” shape, auto deepness adjustment
Bridge	5 – 20 mm Auto Height Adjustment
Perforation	Minimum 1 mm width, Maximum 5 mm depth
Nicking	4 discs auto changer, 0.3 – 0.6 mm width
Dimensions	Main body 290L × 85W × 170H cm; Standard Cassette Holder 90L × 90W × 120H cm
Weight	Main body 800 kg; Standard Cassette Holder 100 kg
Power requirement	230VAC Single Phase 5kW
Compressed air requirement	0.6 – 0.8MPa, 8 mm pipe diameter
Cutting tool	Max 12 tools installed